

Aderendhülsen
























**DIN 46228 Teil 4 für Leiter von 0,14 bis 150mm²
wärmebeständig bis 105° C
Einführungstrichter aus Polyamid halogenfrei**

Querschnitt in mm ²	Kenn-Farbe A	Kenn-Farbe B	Kenn-Farbe DIN*	L1	Maße in mm L2	D1	S1	D2	VE Stück
0,14 AWG 26	■ grau	■ braun							
	60014 N 60014 L	70014 N 70014 L		10,6 12,6	6 8	0,7 0,7	0,15 0,15	1,6 1,6	500/ 10000
0,25 AWG 24	■ hellblau	■ violett							
	60025 N 60025 L	70025 N 60025 L		10,8 12,8	6 8	0,8 0,8	0,15 0,15	1,8 1,8	500/ 10000
0,34 AWG 22	■ türkis	■ pink							
	60034 N 60034 L	70034 N 70034 L		10,8 12,8	6 8	0,9 0,9	0,15 0,15	2 2	500/ 10000
0,5 AWG 22	■ orange	■ weiß	■ weiß						
	60050 K 60050 N 60050 HL 60050 L	70050 K 70050 N 70050 HL 70050 L	70050 K 70050 N 70050 HL 70050 L	12,5 14,5 16,5 18,5	6 8 10 12	1,1 1,1 1,1 1,1	0,15 0,15 0,15 0,15	2,6 2,6 2,6 2,6	500/ 10000
0,75 AWG 20	■ weiß	■ hellblau	■ grau						
	60075 K 60075 N 60075 HL 60075 L	70075 K 70075 N 70075 HL 70075 L	80075 K 80075 N 80075 HL 80075 L	12,5 14,5 16,5 18,5	6 8 10 12	1,3 1,3 1,3 1,3	0,15 0,15 0,15 0,15	2,8 2,8 2,8 2,8	500/ 10000
1,00 AWG 18	■ gelb	■ rot	■ rot						
	60100 K 60100 N 60100 HL 60100 L	70100 K 70100 N 70100 HL 70100 L	70100 K 70100 N 70100 HL 70100 L	12,5 14,5 16,5 18,5	6 8 10 12	1,5 1,5 1,5 1,5	0,15 0,15 0,15 0,15	3 3 3 3	500/ 10000
1,5 AWG 16	■ rot	■ schwarz	■ schwarz						
	60150 K 60150 N 60150 HL 60150 L	70150 K 70150 N 70150 HL 70150 L	70150 K 70150 N 70150 HL 70150 L	12,5 14,5 16,5 24,5	6 8 10 18	1,8 1,8 1,8 1,8	0,15 0,15 0,15 0,15	3,5 3,5 3,5 3,5	500/ 10000
2,5 AWG 14	■ blau	■ grau	■ blau						
	60250 N 60250 HL 60250 L	70250 N 70250 HL 70250 L	60250 N 60250 HL 60250 L	15 19 25	8 12 18	2,3 2,3 2,3	0,15 0,15 0,15	4,2 4,2 4,2	500/ 10000
4,0 AWG 12	■ grau	■ orange	■ grau						
	60400 N 60400 HL 60400 L	70400 N 70400 HL 70400 L	60400 N 60400 HL 60400 L	17 19 25	10 12 18	2,9 2,9 2,9	0,15 0,15 0,15	4,8 4,8 4,8	500/ 10000
6,0 AWG 10	■ schwarz	■ grün	■ gelb						
	60600 N 60600 L	70600 N 70600 L	80600 N 80600 L	20 26	12 18	3,6 3,6	0,2 0,2	6,3 6,3	100/ 5000

Aderendhülsen

**DIN 46228 Teil 4 für Leiter von 0,14 bis 150 mm²
wärmebeständig bis 105° C
Einführungstrichter aus Polyamid, halogenfrei**

Querschnitt in mm ²	Kenn- Farbe A	Kenn- Farbe B	Kenn- Farbe DIN*	L1	Maße in mm L2	D1	S1	D2	VE Stück
10,0 AWG 8	elfenbein 	braun 	rot 						
				61000 N 61000 L	71000 N 71000 L	81000 N 81000 L	21,5 27,5	12 18	4,6 4,6
16,0 AWG 6	grün 	elfenbein 	blau 						
				61600 N 61600 L	71600 N 71600 L	81600 N 71600 L	22,5 28,5	12 18	6 6
25,0 AWG 49	braun 	schwarz 	gelb 						
				62500 N 62500 L	72500 N 72500 L	82500 N 82500 L	29 35	16 22	7,5 7,5
35,0 AWG 2	beige 	rot 	rot 						
				63500N 63500 L	73500 N 73500 L	73500 N 73500 L	30 39	16 25	8,4 8,4
50,0 AWG 1	oliv 	blau 	blau 						
				65000 N 65000 L	75000N 75000 L	75000N 75000 L	36 46	20 30	10,4 10,4
70,0 AWG 2/0	gelb 	gelb 							
				37	25	13,5	0,40	16	25/100
95,0 AWG 3/0	rot 	rot 							
				49	25	14,7	0,40	18	25/100
120,0 AWG 4/0		blau 							
				50	30	16,5	0,50	21	50/100
150,0 AWG 5/0		gelb 							
				54	32	18,5	0,5	23,5	50/100

TWIN Aderendhülsen



TWIN-Aderendhülsen für Leiter von 2x0,5-2x16 mm²
wärmebeständig bis 105° C
Einführungstrichter aus Polyamid halogenfrei

Querschnitt in mm ²	Kenn-Farbe A	Kenn-Farbe B	Kenn-Farbe DIN*	L1	Maße in mm L2	D1	S1	D2	VE Stück
2 x 0,5 AWG 2 x 22	orange 2050 N	weiß 2050 N	weiß 2050 N	15	8	1,4	0,15	0,30	100/1000
2 x 0,75 AWG 2 x 20	weiß 2075 W-N 2075 W-L	blau 2075 B-N 2075 B-L	grau 2075 N 2075 L	15 19	8 12	1,7 1,7	0,15 0,15	0,30 0,30	100/1000
2 x 1,0 AWG 2 x 18	gelb 2100 G-N 2100 G-L	rot 2100 N 2100 L	rot 2100 N 2100 L	16 20	8 12	2,0 2,0	0,15 0,15	0,30 0,30	100/1000
2 x 1,5 AWG 2 x 16	rot 2150 R-N 2150 R-L	schwarz 2150 N 2150 L	schwarz 2150 N 2150 L	16 20	8 12	2,2 2,2	0,15 0,15	0,30 0,30	100/1000
2 x 2,5 AWG 2 x 14	blau 2250 N	grau 2250 G-N	blau 2250 N	19	9	2,8	0,15	0,40	100/1000
2 x 4,0 AWG 2 x 12	grau 2400 N	orange 2400 O-N	grau 2400 N	23	12	3,5	0,20	0,50	100/1000
2 x 6,0 AWG 2 x 10	schwarz 2600 S-N	grün 2600 Gr-N	gelb 2600 N	23	12	4,5	0,20	0,50	100/1000
2 x 10,0 AWG 2 x 8	elfenbein 2110 E-N	brau 2110 B-N	rot 2110 N	26	14	5,8	0,20	0,50	100/1000
2 x 16,0 AWG 2 x 6	grün 2160 G-N	elfenbein 2160 E-N	blau 2160 N	30	14	8,3	0,30	0,60	100/1000